

## ING-AD


Lavov recessed inground floor from the family ING-AD adjustable, with a power of 5,3W and a 40 degrees beam angle. Finished in Stainless steel colour.Dimensions ø130x133mm. With a total lumen output of 465lm and a luminous efficiency of 87,73lm/W. CCT 3000. Driver ON-OFF. Made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover. IP67. IK10

| | |
|---|---|
| **Item code** | **86.OI20.2341.07** |
| **Product type** | **Outdoor** |
| **Category** | **Recessed Inground Floor** |
| **Family** | **ING** |
| **Subfamily** | **ING-AD** |
| **Pictograms** |  |




| **Dimensions** | |
|---|---|
| **Product dimensions (mm)** | **ø130x133mm** |

**Scheme**





**Photometry**





| **Product** | |
|---|---|
| **Real power (W)** | **5.3** |
| **Real luminous flux (Lm)** | **465** |
| **Luminous efficiency (Lm/W)** | **87.73** |
| **Beam angle (º)** | **40** |
| **Life time (h)** | **50000h L80B10** |
| **IP** | **67** |
| **Electrical class insulation** | **Class I** |
| **Colour** | **Stainless steel** |
| **Control gear included** | **Yes** |
| **Control gear** | **ON-OFF** |
| **Light source** | **2x3W CREE** |
| **Colour temperature (K)** | **3000** |
| **Colour consistency (SDCM)** | **SDCM3** |
| **CRI** | **80** |
| **IK** | **IK10** |