

**ING-AD**

Lavov recessed inground floor from the family ING-AD adjustable, with a power of 25.8W and a 60 degrees beam angle. Finished in Stainless steel colour. Dimensions $\varnothing 210 \times 181 \text{ mm}$. With a total lumen output of 1850lm and a luminous efficiency of 71.7lm/W. CCT 3000. Driver ON-OFF. Made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover. IP67. IK10

Dimensions**Product dimensions (mm)** $\varnothing 210 \times 181 \text{ mm}$

Item code	86.OI20.5351.07					
Product type	Outdoor					
Category	Recessed Inground Floor					
Family	ING					
Subfamily	ING-AD					
Pictograms		50 60 Hz	220 240 V		IK 10	
	CRI 80	SDCM 3	CE	Driver INCL.		
	IP 66	50000h L80B10				

Product	
Real power (W)	25.8
Real luminous flux (Lm)	1850
Luminous efficiency (Lm/W)	71.7
Beam angle (°)	60
Life time (h)	50000h L80B10
IP	67
Electrical class insulation	Class I
Colour	Stainless steel
Control gear included	Yes
Control gear	ON-OFF
Light source	9X3W CREE
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80
IK	IK10