




Dimensions












Product dimensions (mm) $\varnothing 250 \times 190 \text{ mm}$

Scheme



ING-AD

Lavov recessed inground floor from the family ING-AD adjustable, with a power of 37.6W and a 3 degrees beam angle. Finished in Stainless steel colour. Dimensions $\varnothing 250 \times 190 \text{ mm}$. With a total lumen output of 2800lm and a luminous efficiency of 74.5lm/W. CCT 3000. Driver ON-OFF. Made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover. IP67. IK10

Item code	86.OI20.6311.07
Product type	Outdoor
Category	Recessed Inground Floor
Family	ING
Subfamily	ING-AD
Pictograms	<div><div>50 60 Hz</div><div>220 240 V</div><div>850°</div><div>IK 10</div><div>CRI 80</div><div>SDCM 3</div><div>CE</div><div>Driver INCL.</div><div>IP 66</div><div>50000h L80B10</div><div></div></div>

Product	
Real power (W)	37.6
Real luminous flux (Lm)	2800
Luminous efficiency (Lm/W)	74.5
Beam angle (°)	3
Life time (h)	50000h L80B10
IP	67
Electrical class insulation	Class I
Colour	Stainless steel
Control gear included	Yes
Control gear	ON-OFF
Light source	18X2W CREE
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80
IK	IK10