



**ING-AD**

Lavov recessed in-ground floor from the family ING-AD adjustable, with a power of 37.6W and a 60 degrees beam angle. Finished in Stainless steel colour. Dimensions  $\varnothing 250 \times 190 \text{mm}$ . With a total lumen output of 2800lm and a luminous efficiency of 74.5lm/W. CCT 3000. Driver ON-OFF. Made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover. IP67. IK10

**Dimensions**

Product dimensions (mm)  $\varnothing 250 \times 190 \text{mm}$

**Scheme**



Item code	86.OI20.6351.07
Product type	Outdoor
Category	Recessed Inground Floor
Family	ING
Subfamily	ING-AD
Pictograms	

<b>Product</b>	
Real power (W)	37.6
Real luminous flux (Lm)	2800
Luminous efficiency (Lm/W)	74.5
Beam angle (&ordm;)	60
Life time (h)	50000h L80B10
IP	67
Electrical class insulation	Class I
Colour	Stainless steel
Control gear included	Yes
Control gear	ON-OFF
Light source	18X2W CREE
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3
CRI	80
IK	IK10