



**ING-M**


Recessed Inground Floor from the family ING-M with a power of 8,5W and a beam angle of 18 degrees. with a real lumen output of 744 lm, and an efficiency of 87,53 lm/W, made in Die Cast Aluminium Body, Front Ring Stainless Steel. , Tempered Glass Cover and finished in Stainless Steel. ON-OFF driver.

|                     |                                |
|---------------------|--------------------------------|
| <b>Item code</b>    | <b>86.OIN3.1311.07</b>         |
| <b>Product type</b> | <b>Outdoor</b>                 |
| <b>Category</b>     | <b>Recessed Inground Floor</b> |
| <b>Family</b>       | <b>ING</b>                     |
| <b>Subfamily</b>    | <b>ING-M</b>                   |


**Pictograms**



**Scheme**



**Photometry**



**Product**

|                                    |                        |
|------------------------------------|------------------------|
| <b>Real power (W)</b>              | <b>8.5</b>             |
| <b>Real luminous flux (Lm)</b>     | <b>744</b>             |
| <b>Luminous efficiency (Lm/W)</b>  | <b>87.53</b>           |
| <b>Beam angle (°)</b>              | <b>18</b>              |
| <b>Life time (h)</b>               | <b>50000h L80B10</b>   |
| <b>IP</b>                          | <b>66</b>              |
| <b>Electrical class insulation</b> | <b>Class I</b>         |
| <b>Colour</b>                      | <b>Stainless steel</b> |
| <b>Control gear included</b>       | <b>Yes</b>             |
| <b>Control gear</b>                | <b>ON-OFF</b>          |
| <b>Light source</b>                | <b>7W COB Nichia</b>   |
| <b>Colour temperature (K)</b>      | <b>3000</b>            |
| <b>Colour consistency (SDCM)</b>   | <b>SDCM &lt; 3</b>     |
| <b>CRI</b>                         | <b>80</b>              |
| <b>IK</b>                          | <b>09</b>              |