



ING-XL

Recessed Inground Floor from the family ING-XL with a power of 18,5W and a beam angle of 38 degrees. with a real lumen output of 1530 lm, and an efficiency of 82,7 lm/W, made in Die Cast Aluminium Body, Front Ring Stainless Steal. , Tempered Glass Cover and finished in Stainless Steal. ON-OFF driver.

| Item code | 86.OIN5.1331.07 |
|--------------|---------------------------|
| Product type | Outdoor |
| Category | Recessed Inground Floor |
| Family | ING |
| Subfamily | ING-XL |
| Pictograms | 50 Hz 220 V SI 10 |
| | CRI SDCM C C Driver INCL. |
| | IP 50000h 66 L80B10 |

| Product | |
|-----------------------------|------------------|
| Real power (W) | 18.5 |
| Real luminous flux (Lm) | 1530 |
| Luminous efficiency (Lm/W) | 82.7 |
| Beam angle (º) | 38 |
| Life time (h) | 50000h L80B10 |
| IP | 66 |
| Electrical class insulation | Class I |
| Colour | Stainless steel |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Light source | 1x18W Nichia COB |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |
| IK | 10 |

Scheme



Photometry



