




**ING-ASSY**


Recessed Inground Floor from the family ING-ASSY with a power of 4,5W and an assymetric beam angle of 27 degrees. with a real lumen output of ? lm, and an efficiency of ? lm/W, made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover and finished in Stainless steel.On-Off driver.

<b>Item code</b>	<b>86.OIN6.1351.07</b>
<b>Product type</b>	<b>Outdoor</b>
<b>Category</b>	<b>Recessed Inground Floor</b>
<b>Family</b>	<b>ING-ASSY</b>
<b>Pictograms</b>	

**Scheme**



**Photometry**



**Product**

<b>Real power (W)</b>	<b>4.5W</b>
<b>Real luminous flux (Lm)</b>	<b>220.5</b>
<b>Beam angle (°)</b>	<b>Asymmetric 27°</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>IP67</b>
<b>Electrical class insulation</b>	<b>Class I</b>
<b>Colour</b>	<b>Natural</b>
<b>Control gear included</b>	<b>yes</b>
<b>Control gear</b>	<b>On-Off</b>
<b>Power Factor</b>	<b>On-Off</b>
<b>Flicker Free</b>	<b>Yes</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>CREE COB</b>
<b>Colour temperature (K)</b>	<b>3000K</b>
<b>Colour consistency (SDCM)</b>	<b>&lt;5SDCM</b>
<b>CRI</b>	<b>80</b>
<b>IK</b>	<b>09</b>