





Scheme














Photometry



ING-ASSY

Recessed Inground Floor from the family ING-ASSY with a power of 4,5W and an assymetric beam angle of 27 degrees. with a real lumen output of 220.5 lm, and an efficiency of 71 lm/W, made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover and finished in Stainless steel.On-Off driver.

Item code	86.OIN6.1351.07
Product type	Outdoor
Category	Recessed Inground Floor
Family	ING-ASSY
Pictograms	<div><div>50 60 Hz</div><div>220 240 V</div><div>850°</div><div>IK 09</div><div>CRI 80</div><div></div><div>Driver INCL.</div><div></div><div>SDCM 5</div><div>50000h L80B10</div><div>IP 67</div></div>

Product	
Real power (W)	4.5W
Real luminous flux (Lm)	220.5
Beam angle (°)	Asymmetric 27°
Life time (h)	50000h L80B10
IP	IP67
Electrical class insulation	Class I
Colour	Natural
Control gear included	yes
Control gear	On-Off
Power Factor	On-Off
Flicker Free	Yes
Light source	LED
Type of LED	CREE COB
Colour temperature (K)	3000K
Colour consistency (SDCM)	<5SDCM
CRI	80
IK	09