

MARK-L


Recessed Inground Floor from the family MARK-L with a power of 4W and an assymetric distribution four emmiting window , made in Die Cast Aluminium Body, and finished in Grey. ON-OFF driver.

Item code	86.OIN6.3331.03
Product type	Outdoor
Category	Recessed Inground Floor
Family	MARK
Subfamily	MARK-L
Pictograms	


Product

Real power (W)	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Real luminous flux (Lm)	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Luminous efficiency (Lm/W)	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Beam angle (°)	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Life time (h)	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
IP	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Electrical class insulation	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Operating temperature	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Electrical feeding	Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover
Colour	Grey
Control gear included	Yes
Control gear	ON-OFF
Light source	6x0.5W SMD
Colour temperature (K)	3000
Colour consistency (SDCM)	SDCM<3

Scheme



Photometry



CRI	80
IK	10
