
RECESSED INGROUND FLOOR - ING-ASSY

Item code 86.0IN6.3351.07






Scheme



Photometry

RECESSED INGROUND FLOOR - ING-ASSY





ING-ASSY

Recessed Inground Floor from the family ING-ASSY with a power of 12W and an assymetric beam angle of 27 degrees. with a real lumen output of ? Im, and an efficiency of ? Im/W, made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover and finished in Stainless steel.On-Off driver.

| Item code | 86.0IN6.3351.07 Outdoor | | | | | | |
|--------------|----------------------------|-----------------|-----------------|-----------|-----------------|--|--|
| Product type | | | | | | | |
| Category | Reces | ssed I | ngrou | und Fl | oor | | |
| Family | ING-ASSY | | | | | | |
| Pictograms | | 50 60 Hz | 220 240 V | ≫ 850° | IK 09 | | |
| | CRI 80 | C€ | Driver INCL. | | SDCM 5 | | |
| | 50000h L80 B 10 | IP 67 | | | | | |

| Product | | | |
|-----------------------------|----------------|--|--|
| Real power (W) | 12W | | |
| Real luminous flux (Lm) | 613 | | |
| Beam angle (º) | Asymmetric 27° | | |
| Life time (h) | 50000h L80B10 | | |
| IP | IP67 | | |
| Electrical class insulation | Class I | | |
| Colour | Natural | | |
| Control gear included | yes | | |
| Control gear | On-Off | | |
| Power Factor | On-Off | | |
| Flicker Free | Yes | | |
| Light source | LED | | |
| Type of LED | CREE COB | | |
| Colour temperature (K) | 3000К | | |
| Colour consistency (SDCM) | <5SDCM | | |
| CRI | 80 | | |
| IK | 09 | | |

