




**MARK-S**

Recessed Inground Floor from the family MARK-S with a power of 3W and an assymetric distribution two emmiting window , made in Die Cast Aluminium Body, and finished in Grey. ON-OFF driver.

|                     |                                |
|---------------------|--------------------------------|
| <b>Item code</b>    | <b>86.OIN7.2331.03</b>         |
| <b>Product type</b> | <b>Outdoor</b>                 |
| <b>Category</b>     | <b>Recessed Inground Floor</b> |
| <b>Family</b>       | <b>MARK</b>                    |
| <b>Subfamily</b>    | <b>MARK-S</b>                  |

|                   |  |  |  |  |  |
|-------------------|--|--|--|--|--|
| <b>Pictograms</b> |  |  |  |  |  |
|                   |  |  |  |  |  |
|                   |  |  |  |  |  |

**Scheme**



|                                    |                      |
|------------------------------------|----------------------|
| <b>Product</b>                     |                      |
| <b>Real power (W)</b>              | <b>3</b>             |
| <b>Beam angle (°)</b>              | <b>assymetric</b>    |
| <b>Life time (h)</b>               | <b>50000h L80B10</b> |
| <b>IP</b>                          | <b>67</b>            |
| <b>Electrical class insulation</b> | <b>Class I</b>       |
| <b>Colour</b>                      | <b>Grey</b>          |
| <b>Control gear included</b>       | <b>Yes</b>           |
| <b>Control gear</b>                | <b>ON-OFF</b>        |
| <b>Light source</b>                | <b>1x2W Osram</b>    |
| <b>Colour temperature (K)</b>      | <b>3000</b>          |
| <b>Colour consistency (SDCM)</b>   | <b>SDCM&lt;3</b>     |
| <b>CRI</b>                         | <b>80</b>            |
| <b>IK</b>                          | <b>10</b>            |

**Photometry**

