




LINEAR-SYM

Recessed Inground Floor from the family LINEAR-SYM with a power of 17,5W and a beam angle of 40 degrees. with a real lumen output of 1020 lm, and an efficiency of 58,29 lm/W, made in Extruded Aluminium Body, Die Cast Aluminium End Caps, Tempered Glass Cover and finished in Grey. ON-OFF driver.

| | |
|--------------|-------------------------|
| Item code | 86.OIN8.1331.03 |
| Product type | Outdoor |
| Category | Recessed Inground Floor |
| Family | LINEAR |
| Subfamily | LINEAR-SYM |
| Pictograms | |

| | |
|-----------------------------|---------------|
| Product | |
| Real power (W) | 17.5 |
| Real luminous flux (Lm) | 1020 |
| Luminous efficiency (Lm/W) | 58.29 |
| Beam angle (°) | 40 |
| Life time (h) | 50000h L80B10 |
| IP | 67 |
| Electrical class insulation | Class I |
| Colour | Grey |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Light source | 12x1.5W Osram |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |
| IK | 07 |

Scheme



Photometry

