



**LINEAR-ASSYM**

Recessed Inground Floor from the family LINEAR-ASSYM with a power of 17,5W and a beam angle of 45/35° Asymmetrical with a real lumen output of 1020 lm, and an efficiency of 58,29 lm/W, made in Extruded Aluminium Body, Die Cast Aluminium End Caps, Tempered Glass Cover and finished in Grey. ON-OFF driver.

<b>Item code</b>	<b>86.OIN8.1381.03</b>
<b>Product type</b>	<b>Outdoor</b>
<b>Category</b>	<b>Recessed Inground Floor</b>
<b>Family</b>	<b>LINEAR</b>
<b>Subfamily</b>	<b>LINEAR-ASSYM</b>


**Pictograms**



**Product**

<b>Real power (W)</b>	<b>17.5</b>
<b>Real luminous flux (Lm)</b>	<b>1020</b>
<b>Luminous efficiency (Lm/W)</b>	<b>58.29</b>
<b>Beam angle (°)</b>	<b>45/35° Asymmetrical</b>
<b>Life time (h)</b>	<b>50000h L80B10</b>
<b>IP</b>	<b>67</b>
<b>Electrical class insulation</b>	<b>Class I</b>
<b>Colour</b>	<b>Grey</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>ON-OFF</b>
<b>Light source</b>	<b>12x1.5W Osram</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>
<b>IK</b>	<b>07</b>

**Scheme**



**Photometry**

