



**LINEAR-ASSYM**

Recessed Inground Floor from the family LINEAR-ASSYM with a power of 36,4W and a beam angle of 45/35° Asymmetrical with a real lumen output of 2114 lm, and an efficiency of 58,08 lm/W, made in Extruded Aluminium Body, Die Cast Aluminium End Caps, Tempered Glass Cover and finished in Grey. ON-OFF driver.

**Item code 86.OIN8.2381.03**

**Product type Outdoor**

**Category Recessed Inground Floor**

**Family LINEAR**

**Subfamily LINEAR-ASSYM**

**Pictograms**

	50 60 Hz	220 240 V		CRI 80
SDCM 3	CE	Driver INCL.		50000h L80B10
IK 07	IP 67			

**Product**

**Real power (W) 36.4**

**Real luminous flux (Lm) 2114**

**Luminous efficiency (Lm/W) 58.08**

**Beam angle (°) 45/35° Asymmetrical**

**Life time (h) 50000h L80B10**

**IP 67**

**Electrical class insulation Class I**

**Colour Grey**

**Control gear included Yes**

**Control gear ON-OFF**

**Light source 24x1.5W Osram**


**Colour temperature (K) 3000**

**Colour consistency (SDCM) SDCM<3**

**CRI 80**

**IK 07**

**Scheme**



**Photometry**

