



LINEAR

Lavov recessed in-ground floor from the family LINEAR, with a power of 84W and a 15*60 degrees beam angle. Finished in Stainless steel colour. Dimensions 55x80x1000mm. With a total lumen output of 2780lm and a luminous efficiency of 33lm/W. CCT RGBW 4 in 1K. Driver not included. Made in Die Cast Aluminium Body, Front Ring stainless Steel, Tempered Glass Cover. IP67. IK07

| Dimensions | |
|-------------------------|--------------|
| Product dimensions (mm) | 55x80x1000mm |

| Scheme | |
|--------|--|
|--------|--|



| | |
|--------------|-------------------------|
| Item code | 86.OIN8.3078.03 |
| Product type | Outdoor |
| Category | Recessed Inground Floor |
| Family | LINEAR |
| Pictograms | |

| | |
|-----------------------------|-----------------|
| Product | |
| Real power (W) | 84 |
| Real luminous flux (Lm) | 2780 |
| Luminous efficiency (Lm/W) | 33 |
| Beam angle (°) | 15*45 |
| Life time (h) | 50000h L80B10 |
| IP | 67 |
| Electrical class insulation | Class I |
| Colour | Stainless steel |
| Control gear included | Yes |
| Control gear | not included |
| Light source | LED |
| Type of LED | 24x2.0W Osram |
| Colour temperature (K) | RGBW 4 in 1 |
| Colour consistency (SDCM) | SDCM3 |
| CRI | 80 |
| IK | IK07 |