




DOWN


Recessed Wall & Ceiling fixture from the family DOWN with a power of 8,8W and an 55° lighting distribution. Real lumen output 1036lm and a luminous efficiency of 117.73lm/W .Made in Die Cast Aluminium Body, Tempered Glass Cover and finished in White powder coating. .IP65, IK07 degree of protection.ON-OFF driver.

| Item code | 86.ORC1.1341.01 |
|--------------|--|
| Product type | Outdoor |
| Category | Recessed Wall & Ceiling |
| Family | DOWN |
| Pictograms | (☐) 50 Hz 220 V 60 Hz 240 V 240 V 850° 80 |
| | SDCM 3 CE Driver INCL. 50000F |
| | IP IK 65 08 |

Scheme



Photometry



| Product | |
|-----------------------------|-------------------|
| Real power (W) | 8.800000000000007 |
| Real luminous flux (Lm) | 1036 |
| Luminous efficiency (Lm/W) | 117.73 |
| Beam angle (º) | 55 |
| Life time (h) | 50000h L70B10 |
| IP | 65 |
| Electrical class insulation | Class I |
| Colour | White |
| U. G. R | <19 |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Flicker Free | Yes |
| Light source | COB CITIZEN |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | >90 |
| IK | 07 |

