



WINDOW


Lavov Recessed wall fixture from the family WINDOW with a power of 9W and an asymmetric beam angle. With a real lumen output of 415LM and a luminous efficacy of 46lm/W. Made in Die cast aluminium body. ABS housing. and finished in grey colour.ON-OFF driver.

| | |
|---------------------|------------------------------------|
| Item code | 86.ORW1.3351.03 |
| Product type | Outdoor |
| Category | Recessed Wall & Ceiling |
| Family | WINDOW |

Pictograms

| | | | | |
|------------------|-------------|--------------|-----------------|----------|
| | 50 60 Hz | 220 240 V | | IK 10 |
| CRI 80 | SDCM 3 | CE | Driver INCL. | |
| 50000h L70B10 | IP 67 | | | |

Scheme



| | |
|------------------------------------|----------------------|
| Product | |
| Real power (W) | 9W |
| Real luminous flux (Lm) | 415LM |
| Luminous efficiency (Lm/W) | 46 |
| Beam angle (°) | Asymmetric |
| Life time (h) | 50000h L70B10 |
| IP | IP65 |
| Electrical class insulation | Class I |
| Colour | grey |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Power Factor | >0,11 |
| Flicker Free | Yes |
| Light source | LED |
| Type of LED | COB |
| Colour temperature (K) | 3000K |
| Colour consistency (SDCM) | SDCM<5 |
| CRI | 80 |
| IK | IK10 |