

**WALLR**

Recessed Wall & Ceiling fixture from the family WALLR with a power of 6.8W and an Diffuse lighting distribution. Real lumen output 90lm and a luminous efficiency of 13.24lm/W .Made in Die Cast Aluminium Body, Front Ring Stainless Steel, Tempered Glass Cover and finished in natural stainless Steel .IP65, IK10 degree of protection.ON-OFF driver.

<b>Item code</b>	<b>86.ORW9.1301.07</b>
<b>Product type</b>	<b>Outdoor</b>
<b>Category</b>	<b>Recessed Wall &amp; Ceiling</b>
<b>Family</b>	<b>WALLR</b>


**Pictograms**

	50 60 Hz	220 240 V		<b>CRI</b> 80
<b>SDCM</b> 3		Driver INCL.		50000h L70B10
<b>IP</b> 65	<b>IK</b> 09/10			

**Product**

<b>Real power (W)</b>	<b>6.8</b>
<b>Real luminous flux (Lm)</b>	<b>90</b>
<b>Luminous efficiency (Lm/W)</b>	<b>13.24</b>
<b>Beam angle (°)</b>	<b>120</b>
<b>Life time (h)</b>	<b>50000h L70B10</b>
<b>IP</b>	<b>65</b>
<b>Electrical class insulation</b>	<b>Class I</b>
<b>Colour</b>	<b>natural stainless Steel</b>
<b>Chip Brand</b>	<b>Epistar</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>ON-OFF</b>
<b>Flicker Free</b>	<b>Yes</b>
<b>Light source</b>	<b>54 SMD</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM&lt;3</b>
<b>CRI</b>	<b>80</b>
<b>IK</b>	<b>IK10</b>

**Scheme**



**Photometry**

