



WALLR

Recessed Wall & Ceiling fixture from the family WALLR with a power of 6.8W and an Diffuse lighting distribution. Real lumen output 132lm and a luminous efficiency of 19.41lm/W .Made in Die Cast Aluminium Body, Front Ring Stainless Steel, Tempered Glass Cover and finished in natural stainless Steel .IP65, IK09 degree of protection.ON-OFF driver.

Item code	86.ORW9.2301.07
------------------	------------------------

Product type	Outdoor
---------------------	----------------

Category	Recessed Wall & Ceiling
-----------------	------------------------------------

Family	WALLR
---------------	--------------

Pictograms	
-------------------	--

Product	
----------------	--

Real power (W)	6.8
-----------------------	------------

Real luminous flux (Lm)	132
--------------------------------	------------

Luminous efficiency (Lm/W)	19.41
-----------------------------------	--------------

Beam angle (°)	120
-----------------------	------------

Life time (h)	50000h L70B10
----------------------	----------------------

IP	65
-----------	-----------

Electrical class insulation	Class I
------------------------------------	----------------

Colour	natural stainless Steel
---------------	--------------------------------

Chip Brand	Epistar
-------------------	----------------

Control gear included	Yes
------------------------------	------------

Control gear	ON-OFF
---------------------	---------------

Flicker Free	Yes
---------------------	------------

Light source	54 SMD
---------------------	---------------

Type of LED	Epistar chip IC driver
--------------------	-------------------------------


Colour temperature (K)	3000
-------------------------------	-------------

Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	80
------------	-----------

IK	IK09
-----------	-------------

Scheme



Photometry

