



## **WALLR**

Recessed Wall & Ceiling fixture from the family WALLR with a power of 6.8W and an Diffuse lighting distribution. Real lumen output 132lm and a luminous efficiency of 19.41lm/W . Made in Die Cast Aluminium Body, Front Ring Stainless Steel, Tempered Glass Cover and finished in natural stainless Steel .IP65, IK09 degree of protection.ON-OFF driver.

Scheme					
92 -	255	0	- 02 -		340
. 47				0	81.

Item code	86.ORW9.2301.07							
Product type	Outdoor  Recessed Wall & Ceiling							
Category								
Family	WALLR							
Pictograms		50 60 Hz	<sup>220</sup> <sub>240</sub> V	∑  850°	CRI 80			
	SDCM 3	ce	Driver INCL.		50000h L70 <b>B</b> 10			
	IP 65	IK 09/10						

## **Photometry**

Product				
Real power (W)	6.8			
Real luminous flux (Lm)	132			
Luminous efficiency (Lm/W)	19.41			
Beam angle (º)	120			
Life time (h)	50000h L70B10			
IP	65			
Electrical class insulation	Class I			
Colour	natural stainless Steel			
Chip Brand	Epistar			
Control gear included	Yes			
Control gear	ON-OFF			
Flicker Free	Yes			
Light source	54 SMD			
Type of LED	Epistar chip IC driver			
Colour temperature (K)	3000			
Colour consistency (SDCM)	SDCM<3			
CRI	80			
IK	IK09			

