



**WALLR**

Recessed Wall & Ceiling fixture from the family WALLR with a power of 6.8W and an Diffuse lighting distribution. Real lumen output 132lm and a luminous efficiency of 19.41lm/W .Made in Die Cast Aluminium Body, Front Ring Stainless Steel, Tempered Glass Cover and finished in natural stainless Steel .IP65, IK09 degree of protection.ON-OFF driver.

**Item code** 86.ORW9.2301.07

**Product type** Outdoor

**Category** Recessed Wall & Ceiling

**Family** WALLR

**Pictograms**

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

**Product**

**Real power (W)** 6.8

**Real luminous flux (Lm)** 132

**Luminous efficiency (Lm/W)** 19.41

**Beam angle (°)** 120

**Life time (h)** 50000h L70B10

**IP** 65

**Electrical class insulation** Class I

**Colour** natural stainless Steel

**Chip Brand** Epistar

**Control gear included** Yes

**Control gear** ON-OFF

**Flicker Free** Yes

**Light source** 54 SMD

**Type of LED** Epistar chip IC driver


**Colour temperature (K)** 3000

**Colour consistency (SDCM)** SDCM<3

**CRI** 80

**IK** IK09

**Scheme**



**Photometry**

