



**WALLR**

Recessed Wall & Ceiling fixture from the family WALLR with a power of 6.8W and an Diffuse lighting distribution. Real lumen output 132lm and a luminous efficiency of 19.41lm/W .Made in Die Cast Aluminium Body, Front Ring Stainless Steel, Tempered Glass Cover and finished in natural stainless Steel .IP65, IK09 degree of protection.ON-OFF driver.

**Item code 86.ORW9.2301.07**

**Product type Outdoor**

**Category Recessed Wall & Ceiling**

**Family WALLR**

**Pictograms**

- 
- 
- 
- 
- 
- 
- 
- 
- 
- 
- 

**Product**

**Real power (W) 6.8**

**Real luminous flux (Lm) 132**

**Luminous efficiency (Lm/W) 19.41**

**Beam angle (°) 120**

**Life time (h) 50000h L70B10**

**IP 65**

**Electrical class insulation Class I**

**Colour natural stainless Steel**

**Chip Brand Epistar**

**Control gear included Yes**

**Control gear ON-OFF**

**Flicker Free Yes**

**Light source 54 SMD**

**Type of LED Epistar chip IC driver**


**Colour temperature (K) 3000**

**Colour consistency (SDCM) SDCM<3**

**CRI 80**

**IK IK09**

**Scheme**



**Photometry**

