



BEAM MODULES

Lavov Spike spot light from the family BEAM with a power of 36 W and a beam angle of 40 degrees with a total lumen output of 2450 lumen and an efficiency of 68,06lm/W. with a CCT of 3000K. Made in die cast aluminum with a front tempered glass, finished in Black color. On-Off driver.

| | |
|------------------|------------------------|
| Item code | 86.OS01.3341.02 |
|------------------|------------------------|

| | |
|---------------------|----------------|
| Product type | Outdoor |
|---------------------|----------------|

| | |
|-----------------|-------------------------|
| Category | Spike Spot Light |
|-----------------|-------------------------|

| | |
|---------------|-------------|
| Family | BEAM |
|---------------|-------------|

| | |
|------------------|---------------------|
| Subfamily | BEAM MODULES |
|------------------|---------------------|


| | |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pictograms |      |
| |      |
| |      |




Dimensions

| | |
|--------------------------------|--------------------------|
| Product dimensions (mm) | 170(Dia)X101(H)mm |
|--------------------------------|--------------------------|

Scheme



Photometry



Product

| | |
|-----------------------|-----------|
| Real power (W) | 36 |
|-----------------------|-----------|

| | |
|--------------------------------|-------------|
| Real luminous flux (Lm) | 2450 |
|--------------------------------|-------------|

| | |
|-----------------------------------|--------------------------|
| Luminous efficiency (Lm/W) | 68.05555555555555 |
|-----------------------------------|--------------------------|

| | |
|-----------------------|-----------|
| Beam angle (°) | 40 |
|-----------------------|-----------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L70B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 66 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Class I |
|------------------------------------|----------------|

| | |
|---------------|--------------|
| Colour | Black |
|---------------|--------------|

| | |
|-------------------|--------------|
| Chip Brand | Osram |
|-------------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON-OFF |
|---------------------|---------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|--------------------|
| Type of LED | 12x3W Osram |
|--------------------|--------------------|

| | |
|------------------------------|----------------------|
| Average life time (h) | 50000h L70B10 |
|------------------------------|----------------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 80 |
|------------|-----------|

| | |
|-----------|-------------|
| IK | IK08 |
|-----------|-------------|