



## VIALIGHT


Street Light from the family VIALIGHTwith a power of 120W and a lighting distribution type T2/T3 with a real lumen output of 15600lm, and an efficiency of 130lm/W, CRI  $\geq$ 70 with a DALI driver, made in Die Cast Aluminium Body, Front Tempered Glass and finished in Grey color

| ltem code    | 86.OS01.7473.03                              |
|--------------|--|
| Product type | Outdoor                                      |
| Category     | Street lights                                |
| Family       | VIALIGHT                                     |
| Pictograms   | (→ 220 v )→ C€ Driver<br>240 v 850° C€ INCL. |
|              | EXE 2 IP CRI 70                              |
|              | SDCM 50000h IK<br>5 L70B10 08                |

## Dimensions

Product dimensions (mm) 585\*288\*137

## Scheme



| Product                     |                    |
|-----------------------------|--------------------|
| Real power (W)              | 120                |
| Real luminous flux (Lm)     | 15600              |
| Luminous efficiency (Lm/W)  | 130                |
| Beam angle (º)              | T2/T3              |
| Life time (h)               | 50000h L70B10      |
| IP                          | 66                 |
| Electrical class insulation | Class I            |
| Colour                      | Grey               |
| Control gear included       | Yes                |
| Control gear                | DALI               |
| Type of LED                 | Lumileds / SMD3030 |
| Colour temperature (K)      | 4000               |
| Colour consistency (SDCM)   | SDCM<5             |
| CRI                         | ≥70                |
| IK                          | 09                 |

