




VIALIGHT

Street Light from the family VIALIGHTwith a power of 240W and a lighting distribution type T2/T3 with a real lumen output of 31200lm, and an efficiency of 130lm/W, CRI \geq 70 with a DALI driver, made in Die Cast Aluminium Body, Front Tempered Glass and finished in Grey color

| Item code | 86.OS01.B473.03 |
|--------------|--|
| Product type | Outdoor |
| Category | Street lights |
| Family | VIALIGHT |
| Pictograms | (→ 220 v)→ C€ Driver 240 v 850° C€ INCL. |
| | EXE (P) CRI 66 70 |
| | SDCM 50000h IK 5 L70B10 08 |

Scheme



| Product | |
|-----------------------------|--------------------------|
| Real power (W) | 240 |
| Real luminous flux (Lm) | 31200 |
| Luminous efficiency (Lm/W) | 130 |
| Beam angle (º) | T2/T3 |
| Life time (h) | 50000h L70B10 |
| IP | 66 |
| Electrical class insulation | Class I |
| Colour | Grey |
| Control gear included | Yes |
| Control gear | DALI |
| Type of LED | LUMILEDS 3030 |
| Average life time (h) | Up to 100,000hrs LM70,Ta |
| | 25°C |
| Colour temperature (K) | 3000K |
| Colour consistency (SDCM) | <4 |
| CRI | >70 |
| к | IK10 |
| | |

