



TUBE0-R

Lavov spike spot light from the family TUBE0-R with a power of 4W and a 15 degrees beam angle. With a total lumen output of 340lm and a luminous efficiency of 85lm/W. Made in Die Cast Aluminum body, steel bracket and Tempered Glass cover and finished in White colour. IP67 and IK10 degree of protection ON-OFF driver.

| | | | | | | |
|--------------|------------------|--|--|--|--|--|
| Item code | 86.OS04.1321.01 | | | | | |
| Product type | Outdoor | | | | | |
| Category | Spike Spot Light | | | | | |
| Family | TUBE0-R | | | | | |
| Subfamily | TUBE0-R | | | | | |
| Pictograms | | | | | | |
| | | | | | | |
| | | | | | | |

| | |
|-----------------------------|----------------|
| Product | |
| Real power (W) | 4 |
| Real luminous flux (Lm) | 340 |
| Luminous efficiency (Lm/W) | 85 |
| Beam angle (°) | 15 |
| Life time (h) | 50000h L70B10 |
| IP | 67 |
| Electrical class insulation | Class II |
| Colour | White |
| Control gear included | Yes |
| Control gear | ON-OFF |
| Light source | LED |
| Type of LED | 1x4W CREE 1304 |
| Average life time (h) | 50000h L70B10 |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |
| IK | IK10 |

Dimensions

Product dimensions (mm) 43(Dia)X65(H)mm

Scheme

