



## **TUBEO-S**

Lavov spike spot light from the family TUBEO-S with a power of  $% \left\{ 1,2,...,n\right\}$ 6W and a 55 degrees beam angle. With a total lumen output of 484lm and a luminous efficiency of 80.67lm/W. Made in Die Cast Aluminum body, steel bracket and Tempered Glass cover and finished in Black colour. IP67 and IK10 degree of protection ON-OFF driver.

| Item code    | 86.OS05.2351.02               |
|--------------|-------------------------------|
| Product type | Outdoor                       |
| Category     | Spike Spot Light              |
| Family       | TUBEO-S                       |
| Subfamily    | TUBEO-S                       |
| Pictograms   | CRI SDCM 80 3 C €             |
|              | Driver On 50000h IP L70B10 65 |
|              | → <b>IK</b> 335° 90° 05       |

| Item code    | 86.OS05.2351.02               |
|--------------|-------------------------------|
| Product type | Outdoor                       |
| Category     | Spike Spot Light              |
| Family       | TUBEO-S                       |
| Subfamily    | TUBEO-S                       |
| Pictograms   | CRI SDCM 3                    |
|              | Driver On S0000h IP L70B10 65 |
|              | →                             |

| ı   | 90 8   | 66 |
|-----|--------|----|
| 114 |        |    |
| ,   | - 30 - | 56 |
|     |        |    |

50X50X90(H)mm

| Product                     |                |
|-----------------------------|----------------|
| Real power (W)              | 6              |
| Real luminous flux (Lm)     | 484            |
| Luminous efficiency (Lm/W)  | 80.67          |
| Beam angle (º)              | 55             |
| Life time (h)               | 50000h L70B10  |
| IP                          | 67             |
| Electrical class insulation | Class II       |
| Colour                      | Black          |
| Control gear included       | Yes            |
| Control gear                | ON-OFF         |
| Light source                | LED            |
| Type of LED                 | 1x6W CREE 1304 |
| Average life time (h)       | 50000h L70B10  |
| Colour temperature (K)      | 3000           |
| Colour consistency (SDCM)   | SDCM<3         |
| CRI                         | 80             |
| IK                          | IK10           |



**Dimensions** 

Scheme

**Product dimensions (mm)**