




### TUBEO-S


Lavov spike spot light from the family TUBEO-S with a power of 6W and a 55 degrees beam angle. With a total lumen output of 484lm and a luminous efficiency of 80.67lm/W. Made in Die Cast Aluminum body, steel bracket and Tempered Glass cover and finished in Black colour. IP67 and IK10 degree of protection ON-OFF driver.

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Item code    | 86.OS05.2351.02                                                                      |
| Product type | Outdoor                                                                              |
| Category     | Spike Spot Light                                                                     |
| Family       | TUBEO-S                                                                              |
| Subfamily    | TUBEO-S                                                                              |
| Pictograms   |  |

### Dimensions

Product dimensions (mm) 50X50X90(H)mm

### Scheme



|                             |                |
|-----------------------------|----------------|
| Product                     |                |
| Real power (W)              | 6              |
| Real luminous flux (Lm)     | 484            |
| Luminous efficiency (Lm/W)  | 80.67          |
| Beam angle (°)              | 55             |
| Life time (h)               | 50000h L70B10  |
| IP                          | 67             |
| Electrical class insulation | Class II       |
| Colour                      | Black          |
| Control gear included       | Yes            |
| Control gear                | ON-OFF         |
| Light source                | LED            |
| Type of LED                 | 1x6W CREE 1304 |
| Average life time (h)       | 50000h L70B10  |
| Colour temperature (K)      | 3000           |
| Colour consistency (SDCM)   | SDCM<3         |
| CRI                         | 80             |
| IK                          | IK10           |