


## Vector

Lavov outdoor spot light from the family Vector with a power of 24W and a 25 degrees beam angle. Surface mounted installation With a total lumen output of 1680lm and a luminous efficiency of 70lm/W. Driver ON-OFF .Made in Die cast aluminum body + Tempered glass . Powder coated,. Class I issolation. IP65 and IK07 . Mains voltage 220-240V. Finished in grey colour. CCT 3000K.CRI80

| | |
|---|---|
| **Item code** | **86.OS06.7331.03** |
| **Product type** | **Outdoor** |
| **Category** | **Spike Spot Light** |
| **Family** | **Vector** |
| **Pictograms** |  |

| | |
|---|---|
| **Dimensions** | |
| **Product dimensions (mm)** | **115x115x105xH190mm** |

**Scheme**




| | |
|---|---|
| **Product** | |
| **Real power (W)** | **24** |
| **Real luminous flux (Lm)** | **1680** |
| **Luminous efficiency (Lm/W)** | **70** |
| **Beam angle (º)** | **25** |
| **Life time (h)** | **50000h L70B10** |
| **IP** | **65** |
| **Electrical class insulation** | **Class I** |
| **Electrical feeding** | **220-240V** |
| **Colour** | **grey** |
| **Control gear included** | **Yes** |
| **Control gear** | **ON-OFF** |
| **Light source** | **LED** |
| **Average life time (h)** | **50000h L70B10** |
| **Colour temperature (K)** | **3000** |
| **Colour consistency (SDCM)** | **SDCM3** |
| **CRI** | **80** |
| **IK** | **7** |