



VILA P27

Lavov Street Light from the family VILA with a power of 80W and a lighting distribution type T2A with a real lumen output of 9067,82 lm, and an efficiency of 113,34 lm/W, CRI ≥ 70 with a ON-OFF driver, made in steel Body, Front Tempered Glass and finished in Black color. Post mounted. Post diam 27mm.

| | |
|------------------|------------------------|
| Item code | 86.OS08.4321.02 |
|------------------|------------------------|

| | |
|---------------------|----------------|
| Product type | Outdoor |
|---------------------|----------------|

| | |
|-----------------|----------------------|
| Category | Street lights |
|-----------------|----------------------|

| | |
|---------------|-------------|
| Family | VILA |
|---------------|-------------|

| | |
|------------------|-----------------|
| Subfamily | VILA P27 |
|------------------|-----------------|

| | |
|-------------------|---|
| Pictograms |      |
|-------------------|---|


220
240 V

850°

CE

Driver
INCL.IP
66CRI
70SDCM
550000h
L70B10

Scheme



Product

| | |
|-----------------------|-----------|
| Real power (W) | 80 |
|-----------------------|-----------|

| | |
|--------------------------------|----------------|
| Real luminous flux (Lm) | 9067.82 |
|--------------------------------|----------------|

| | |
|-----------------------------------|------------------|
| Luminous efficiency (Lm/W) | 113.34775 |
|-----------------------------------|------------------|

| | |
|---------------|--------------|
| Colour | black |
|---------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | yes |
|------------------------------|------------|

| | |
|---------------------|---------------|
| Control gear | ON-OFF |
|---------------------|---------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|---------------------|
| Type of LED | PHILIPS 5050 |
|--------------------|---------------------|

| | |
|------------------------------|----------------------|
| Average life time (h) | 50000h L70B55 |
|------------------------------|----------------------|

| | |
|-------------------------------|--------------|
| Colour temperature (K) | 3000K |
|-------------------------------|--------------|

| | |
|----------------------------------|--------------|
| Colour consistency (SDCM) | <5 |
|----------------------------------|--------------|

| | |
|------------|---------------|
| CRI | >80 |
|------------|---------------|

| | |
|-----------|-------------|
| IK | IK08 |
|-----------|-------------|

Photometry

