












Voyager II

Lavov Street light from the family Voyager II with a power of 100W and an optics typeT1 . CCT 4000K. With a total lumen output of 15000lm and a luminous efficiency of 150lm/W.DALI driver. Made in die cast aluminum and finished in grey color. IP66 and IK08 degree of protection.

|              |  |
|--------------|--|
| Item code    | 86.OS15.6413.03  |
| Product type | Outdoor  |
| Category     | Street lights  |
| Family       | Voyager II   |
| Pictograms   | <div><div><div>220<br/>240 V</div></div><div><div>850°</div></div><div><div>Driver<br/>INCL.</div></div><div><div>DALI</div></div><div><div>IP<br/>66</div></div><div><div>CRI<br/>70</div></div><div><div>SDCM<br/>5</div></div><div><div>50000h<br/>L70B10</div></div><div><div>IK<br/>08</div></div></div> |

Dimensions

Product dimensions (mm) 600\*243\*120MM

Scheme



|                             |                               |
|-----------------------------|-------------------------------|
| Product                     |                               |
| Real power (W)              | 100                           |
| Real luminous flux (Lm)     | 15000                         |
| Luminous efficiency (Lm/W)  | 150                           |
| Beam angle (°)              | T1                            |
| Life time (h)               | 70000h L70B10                 |
| IP                          | 66                            |
| Electrical class insulation | Class I                       |
| Colour                      | grey                          |
| Control gear included       | yes                           |
| Control gear                | DALI                          |
| Light source                | LED                           |
| Type of LED                 | LUMILEDS 3030                 |
| Average life time (h)       | Up to 100,000hrs LM70,Ta 25°C |
| Colour temperature (K)      | 4000                          |
| Colour consistency (SDCM)   | SDCM<6                        |
| CRI                         | >80                           |
| IK                          | IK08                          |