



Voyager II

Lavov Street light from the family Voyager with a power of 240W and an optics type T3 . CCT 4000K. With a total lumen output of 36000lm and a luminous efficiency of 150lm/W.DALI driver.

Made in die cast aluminum and finished in grey color. IP66 and IK08 degree of protection.


| | |
|------------------|------------------------|
| Item code | 86.OS15.C433.03 |
|------------------|------------------------|

| | |
|---------------------|----------------|
| Product type | Outdoor |
|---------------------|----------------|

| | |
|-----------------|----------------------|
| Category | Street lights |
|-----------------|----------------------|

| | |
|---------------|-------------------|
| Family | Voyager II |
|---------------|-------------------|

Pictograms



Product

| | |
|-----------------------|------------|
| Real power (W) | 240 |
|-----------------------|------------|

| | |
|--------------------------------|--------------|
| Real luminous flux (Lm) | 36000 |
|--------------------------------|--------------|

| | |
|-----------------------------------|------------|
| Luminous efficiency (Lm/W) | 150 |
|-----------------------------------|------------|

| | |
|-----------------------|-----------|
| Beam angle (°) | T3 |
|-----------------------|-----------|

| | |
|----------------------|----------------------|
| Life time (h) | 70000h L70B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 66 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Class I |
|------------------------------------|----------------|

| | |
|---------------|-------------|
| Colour | grey |
|---------------|-------------|

| | |
|------------------------------|------------|
| Control gear included | yes |
|------------------------------|------------|

| | |
|---------------------|-------------|
| Control gear | DALI |
|---------------------|-------------|

| | |
|---------------------|------------|
| Light source | LED |
|---------------------|------------|

| | |
|--------------------|----------------------|
| Type of LED | LUMILEDS 3030 |
|--------------------|----------------------|

| | |
|------------------------------|--------------------------------------|
| Average life time (h) | Up to 100,000hrs LM70,Ta 25°C |
|------------------------------|--------------------------------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 4000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<6 |
|----------------------------------|------------------|

| | |
|------------|---------------|
| CRI | >80 |
|------------|---------------|

| | |
|-----------|-------------|
| IK | IK08 |
|-----------|-------------|

Dimensions

| | |
|--------------------------------|----------------------|
| Product dimensions (mm) | 721*313*120MM |
|--------------------------------|----------------------|

Scheme

