



Quadro

Lavov spike spotlight from the family Quadro with a power of 36W and a 40 degrees beam angle. With a CCT of RGB K. Made of die cast aluminium and finished in grey color. IP66 degree of protection.ON-OFF driver.

| Item code | 86.OSP4.1021.03 | | | | | |
|--------------|-----------------------------------|---------------------------------|------------|-----------|-----------|--|
| Product type | Outdoor | | | | | |
| Category | Spike Spot Light | | | | | |
| Family | Quadro | | | | | |
| Pictograms | | ²²⁰ ₂₄₀ V | > 850° | CRI 80 | SDCM 3 | |
| | C€ | Driver INCL. | On Off | | | |
| | 50000h L 70 B 10 | IP 65 | ⊋ 335° | 7. 90° | IK 05 | |

| Product | | | | |
|-----------------------------|-------------------------|--|--|--|
| Real power (W) | 36 | | | |
| Real luminous flux (Lm) | 2212 | | | |
| Luminous efficiency (Lm/W) | 61.444444444444 | | | |
| Beam angle (º) | 40 | | | |
| IP | 66 | | | |
| Electrical class insulation | Class I | | | |
| Colour | grey | | | |
| Control gear included | YES | | | |
| Control gear | ON-OFF | | | |
| Light source | LED | | | |
| Type of LED | OSRAM "RGB 3in1 DMX512" | | | |
| Average life time (h) | 50000h L70B10 | | | |
| Colour temperature (K) | RGB | | | |
| Colour consistency (SDCM) | SDCM<3 | | | |
| CRI | 80 | | | |
| IK | IK08 | | | |
| | | | | |

Scheme



