




## Quadro

Lavov spike spotlight from the family Quadro with a power of  $% \left( 1\right) =\left( 1\right) \left( 1\right) +\left( 1\right) \left( 1\right) \left( 1\right) +\left( 1\right) \left( 1$ 72W and a 40 degrees beam angle. With a CCT of RGB K. Made of die cast aluminium and finished in grey color. IP66 degree of protection.ON-OFF driver.

Item code	86.OSP4.2021.03		
Product type	Outdoor		
Category	Spike Spot Light		
Family	Quadro		
Pictograms	( <del>=</del> )	<b>9CM</b> 3	
	C € Driver On Off		
	727272	IK 05	

## Scheme



Real power (W) 72  Real luminous flux (Lm) 5085  Luminous efficiency (Lm/W) 70.625  Beam angle (º) 40  IP 66  Electrical class insulation Class I  Colour grey	Product	
Luminous efficiency (Lm/W) 70.625  Beam angle (º) 40  IP 66  Electrical class insulation Class I	Real power (W)	72
Beam angle (°) 40 IP 66 Electrical class insulation Class I	Real luminous flux (Lm)	5085
IP 66 Electrical class insulation Class I	Luminous efficiency (Lm/W)	70.625
Electrical class insulation Class I	Beam angle (º)	40
	IP	66
Colour grey	Electrical class insulation	Class I
	Colour	grey
Control gear included YES	Control gear included	YES
Control gear ON-OFF	Control gear	ON-OFF
Light source LED	Light source	LED
Type of LED OSRAM "RGB 3in1 DMX512"	Type of LED	OSRAM "RGB 3in1 DMX512"
Average life time (h) 50000h L70B10	Average life time (h)	50000h L70B10
Colour temperature (K) RGB	Colour temperature (K)	RGB
Colour consistency (SDCM) SDCM<3	Colour consistency (SDCM)	SDCM<3
CRI 80	CRI	80
IK IK08	IK	IK08

