




Quadro

Lavov spike spotlight from the family Quadro with a power of 30W and a 25 degrees beam angle. With a CCT of 2700 K. Made of die cast aluminium and finished in grey color. IP66 degree of protection.ON-OFF driver.

| Item code | 86.OSP4.2321.03 Outdoor | | | | |
|--------------|---------------------------|-----|-----------|-----------|--|
| Product type | | | | | |
| Category | Spike Spot Light | | | | |
| Family | Quadro | | | | |
| Pictograms | 220 | 0 v | CRI 80 | SDCM 3 | |
| | C € Dri | | | | |
| | 50000h L70 B 10 | P | ₹ 90° | IK 05 | |

| Product | | | |
|-----------------------------|------------------|--|--|
| Real power (W) | 30.69 | | |
| Real luminous flux (Lm) | 2225 | | |
| Luminous efficiency (Lm/W) | 72.4991854024112 | | |
| Beam angle (º) | 25 | | |
| IP | 66 | | |
| Electrical class insulation | Class I | | |
| Colour | grey | | |
| Control gear included | YES | | |
| Control gear | ON-OFF | | |
| Light source | LED | | |
| Type of LED | OSRAM | | |
| Average life time (h) | 50000h L70B10 | | |
| Colour temperature (K) | 3000 | | |
| Colour consistency (SDCM) | SDCM<3 | | |
| CRI | 80 | | |
| IK | IK08 | | |

Scheme



Photometry

