



### WALLLIGHT (OW02)

Wall Washer fixture from the family WALLLIGHT (OW02) with a power of 48W and a lighting distribution of 15°X40° with a real lumen output of 3800lm and an efficiency of 79,17lm/W with a CCT of 3000K, made in Extruded Aluminium, Die Cast End Caps, Tempered Glass Cover and finished in Grey color. DALI driver.

### Scheme



<b>Item code</b>	<b>86.OW02.2363.03</b>
<b>Product type</b>	<b>Outdoor</b>
<b>Category</b>	<b>Wall Washer</b>
<b>Family</b>	<b>WALLLIGHT</b>
<b>Subfamily</b>	<b>WALLLIGHT (OW02)</b>
<b>Pictograms</b>	

<b>Product</b>	
<b>Real power (W)</b>	<b>48</b>
<b>Real luminous flux (Lm)</b>	<b>3800</b>
<b>Luminous efficiency (Lm/W)</b>	<b>79.17</b>
<b>Beam angle (°)</b>	<b>15°X40°</b>
<b>Life time (h)</b>	<b>50000h L70B10</b>
<b>IP</b>	<b>65</b>
<b>Electrical class insulation</b>	<b>Class I</b>
<b>Colour</b>	<b>Grey</b>
<b>Chip Brand</b>	<b>OSRAM</b>
<b>Control gear included</b>	<b>Yes</b>
<b>Control gear</b>	<b>NOT INCLUDED</b>
<b>Light source</b>	<b>LED</b>
<b>Type of LED</b>	<b>OSRAM single color</b>
<b>Colour temperature (K)</b>	<b>3000</b>
<b>Colour consistency (SDCM)</b>	<b>SDCM3</b>
<b>CRI</b>	<b>&gt;80</b>
<b>IK</b>	<b>IK08</b>