



Scheme



WALLLIGHT (OW03)

Wall Washer fixture from the family WALLLIGHT (OW03) with a power of 48W and a lighting distribution of 10° with a real lumen output of 2870lm and an efficiency of 58,79lm/W with a CCT of 3000K, made in Extruded Aluminium, Die Cast End Caps, Tempered Glass Cover and finished in Grey color. DALI driver.

| | |
|--------------|--|
| Item code | 86.OW03.2323.03 |
| Product type | Outdoor |
| Category | Wall Washer |
| Family | WALLLIGHT |
| Subfamily | WALLLIGHT (OW03) |
| Pictograms | <div><div></div><div>50 60 Hz</div><div></div><div>850°</div><div>CRI 80</div><div>SDCM 3</div><div>CE</div><div>Driver EXCL.</div><div>DALI</div><div>50000h L70B10</div><div>IP 65</div><div>IK 08</div><div>90°+90°</div></div> |

| | |
|-----------------------------|--------------------|
| Product | |
| Real power (W) | 48 |
| Real luminous flux (Lm) | 2870 |
| Luminous efficiency (Lm/W) | 58.79 |
| Beam angle (°) | 10° |
| Life time (h) | 50000h L70B10 |
| IP | 65 |
| Electrical class insulation | Class I |
| Colour | Grey |
| Chip Brand | OSRAM |
| Control gear included | Yes |
| Control gear | NOT INCLUDED |
| Light source | OSRAM single color |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | >80 |
| IK | IK08 |