


**Dimensions****Product dimensions (mm)** 32x83x1000mm**Scheme**

Size: Unit (mm)

**Snake SC**

Lavov outdoor spot light from the family Snake SC with a power of 36W and a 30 degrees beam angle. Surface mounted installation With a total lumen output of 2700lm and a luminous efficiency of 75lm/W. Driver DRIVER EXCL not included .Made in Die cast aluminum body + PC transparent cover. Powder coated,. Class III isolation. IP65 and IK08 . Mains voltage DC 24V. Finished in grey colour. CCT 2700K.CRI80

|                     |                                                                                                                                                                                                     |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Item code</b>    | <b>86.OW05.2230.03</b>                                                                                                                                                                              |
| <b>Product type</b> | <b>Outdoor</b>                                                                                                                                                                                      |
| <b>Category</b>     | <b>Wall Washer</b>                                                                                                                                                                                  |
| <b>Family</b>       | <b>Snake</b>                                                                                                                                                                                        |
| <b>Subfamily</b>    | <b>Snake SC</b>                                                                                                                                                                                     |
| <b>Pictograms</b>   | <div>50<br/>60 Hz</div> <div>850°</div> <div>CRI<br/>80</div> <div>SDCM<br/>3</div> <div>CE</div> <div>Driver<br/>EXCL</div> <div>50000h<br/>L70B10</div> <div>IP<br/>65</div> <div>IK<br/>08</div> |

|                                    |                      |
|------------------------------------|----------------------|
| <b>Product</b>                     |                      |
| <b>Real power (W)</b>              | <b>36</b>            |
| <b>Real luminous flux (Lm)</b>     | <b>2700</b>          |
| <b>Luminous efficiency (Lm/W)</b>  | <b>75</b>            |
| <b>Beam angle (°)</b>              | <b>30</b>            |
| <b>Life time (h)</b>               | <b>50000h L70B10</b> |
| <b>IP</b>                          | <b>65</b>            |
| <b>Electrical class insulation</b> | <b>Class III</b>     |
| <b>Electrical feeding</b>          | <b>DC 24V</b>        |
| <b>Colour</b>                      | <b>grey</b>          |
| <b>Control gear included</b>       | <b>not included</b>  |
| <b>Control gear</b>                | <b>DRIVER EXCL</b>   |
| <b>Power Factor</b>                | <b>DRIVER EXCL</b>   |
| <b>Flicker Free</b>                | <b>DRIVER EXCL</b>   |
| <b>Light source</b>                | <b>LED</b>           |
| <b>Type of LED</b>                 | <b>Osram 3030</b>    |
| <b>Average life time (h)</b>       | <b>50000h L70B10</b> |
| <b>Colour temperature (K)</b>      | <b>2700</b>          |
| <b>Colour consistency (SDCM)</b>   | <b>SDCM3</b>         |
| <b>CRI</b>                         | <b>80</b>            |
| <b>IK</b>                          | <b>08</b>            |