



DOWNT

Lavov wall fixture from the family DOWNT with a power of 4.5W and a 24 degrees beam angle. Finished in Black colour. Dimensions  $\varnothing 50 \times 73 \times 120 \text{ mm}$ . With a total lumen output of 457lm and a luminous efficiency of 81lm/W. CCT 3000K. Driver DALI. Made in Die Cast Aluminium Body, Tempered Glass Cover. IP65. IK05


|              |                                                                                                                                                                                                                                             |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code    | 86.OW08.1323.02                                                                                                                                                                                                                             |
| Product type | Outdoor                                                                                                                                                                                                                                     |
| Category     | Wall Fixtures                                                                                                                                                                                                                               |
| Family       | DOWNT                                                                                                                                                                                                                                       |
| Pictograms   | <div><div></div><div>50<br/>60 Hz</div><div></div><div>850°</div><div>CRI<br/>80</div><div>SDCM<br/>3</div><div>CE</div><div>Driver<br/>INCL.</div><div></div><div>50000h<br/>L70B10</div><div>IP<br/>65</div><div>IK<br/>05/10</div></div> |

|                             |               |
|-----------------------------|---------------|
| Product                     |               |
| Real power (W)              | 4.5           |
| Real luminous flux (Lm)     | 457           |
| Luminous efficiency (Lm/W)  | 81            |
| Beam angle (°)              | 24            |
| Life time (h)               | 50000h L70B10 |
| IP                          | IP65          |
| Electrical class insulation | Class I       |
| Colour                      | Black         |
| Control gear included       | Yes           |
| Control gear                | DALI          |
| Light source                | LED           |
| Type of LED                 | COB           |
| Colour temperature (K)      | 3000          |
| Colour consistency (SDCM)   | SDCM<3        |
| CRI                         | 80            |
| IK                          | IK05          |

Dimensions

Product dimensions (mm)  $\varnothing 50 \times 73 \times 120 \text{ mm}$

Scheme



Photometry

