




Dimensions

Product dimensions (mm) 32x83x1000mm

Scheme



Photometry



Snake 3SC

Lavov outdoor spot light from the family Snake 3SC with a power of 72W and a 10 degrees beam angle. Surface mounted installation With a total lumen output of 5400lm and a luminous efficiency of 75lm/W. Driver ON-OFF not included .Made in Die cast aluminum body + PC transparent cover. Powder coated,. Class III isolation. IP65 and IK08 . Mains voltage DC 24V. Finished in grey colour. CCT 2700K.CRI80

|              |                                                                                                                                                                       |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code    | 86.OW08.5210.03                                                                                                                                                       |
| Product type | Outdoor                                                                                                                                                               |
| Category     | Wall Washer                                                                                                                                                           |
| Family       | Snake 3                                                                                                                                                               |
| Subfamily    | Snake 3SC                                                                                                                                                             |
| Pictograms   | <div>50 Hz</div> <div>850°</div> <div>CRI 80</div> <div>SDCM 3</div> <div>CE</div> <div>Driver EXCL.</div> <div>50000h L70B10</div> <div>IP 65</div> <div>IK 08</div> |

|                             |               |
|-----------------------------|---------------|
| Product                     |               |
| Real power (W)              | 72            |
| Real luminous flux (Lm)     | #VALUE!       |
| Luminous efficiency (Lm/W)  | 75            |
| Beam angle (°)              | 10            |
| Life time (h)               | 50000h L70B10 |
| IP                          | 65            |
| Electrical class insulation | Class III     |
| Electrical feeding          | DC 24V        |
| Colour                      | grey          |
| Control gear included       | not included  |
| Control gear                | ON-OFF        |
| Power Factor                | ON-OFF        |
| Flicker Free                | ON-OFF        |
| Light source                | LED           |
| Type of LED                 | Osram 3030    |
| Average life time (h)       | 50000h L70B10 |
| Colour temperature (K)      | 2700          |
| Colour consistency (SDCM)   | SDCM3         |
| CRI                         | 80            |
| IK                          | 8             |