WALL LIGHT - UP&DOWN TUBE






UP&DOWN TUBE

UP&DOWNT is a wall light with round design emitting light up and down. With a size of Ø80mmx200mm has a power of 2x8W and two reflectors up&down of 24 degrees beam angle.With a real lumen output of 1972lm, and an efficiency of 123.25lm/W. Is made in Die Cast Aluminium Body, Tempered Glass Cover and has an IP65 and an IK10 degree of protection. DALI driver. Finished in Black color.

| ltem code | 86.OW09.2323.02 |
|--------------|---|
| Product type | Indoor |
| Category | Wall Light |
| Family | UP&DOWN TUBE |
| Pictograms | (☐) 50 Hz 220 V 50 Hz 240 V 240 V 80 CRI 80 |
| | SDCM CE Driver 50000h 3 CE INCL. 50000h |
| | IP IK 65 05/10 |

| Product | |
|-----------------------------|---------------|
| Real power (W) | 8 |
| Real luminous flux (Lm) | 1972 |
| Luminous efficiency (Lm/W) | 123.25 |
| Beam angle (º) | 24 |
| Life time (h) | 50000h L70B10 |
| IP | 65 |
| Electrical class insulation | Class I |
| Colour | Black |
| Control gear included | Yes |
| Control gear | DALI |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | SDCM<3 |
| CRI | 80 |
| ІК | 10 |

Scheme



Photometry

