



UP&DOWNT

Lavov wall fixture from the family UP&DOWNT with a power of 2x12.5W and a 24 degrees beam angle. Finished in White colour. Dimensions  $\varnothing 75 \times 98 \times 240 \text{ mm}$ . With a total lumen output of 2x1082lm and a luminous efficiency of 86.56lm/W. CCT 3000K. Driver ON-OFF. Made in Die Cast Aluminium Body, Tempered Glass Cover .IP65. IK05


|              |                                                                                                                                                                                                                                             |
|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Item code    | 86.OW09.3321.01                                                                                                                                                                                                                             |
| Product type | Outdoor                                                                                                                                                                                                                                     |
| Category     | Wall Fixtures                                                                                                                                                                                                                               |
| Family       | UP&DOWNT                                                                                                                                                                                                                                    |
| Pictograms   | <div><div></div><div>50<br/>60 Hz</div><div></div><div>850°</div><div>CRI<br/>80</div><div>SDCM<br/>3</div><div>CE</div><div>Driver<br/>INCL.</div><div></div><div>50000h<br/>L70B10</div><div>IP<br/>65</div><div>IK<br/>05/10</div></div> |

|                             |               |
|-----------------------------|---------------|
| Product                     |               |
| Real power (W)              | 2x12.5        |
| Real luminous flux (Lm)     | 2x1082        |
| Luminous efficiency (Lm/W)  | 86.56         |
| Beam angle (°)              | 24            |
| Life time (h)               | 50000h L70B10 |
| IP                          | IP65          |
| Electrical class insulation | Class I       |
| Colour                      | White         |
| Control gear included       | Yes           |
| Control gear                | ON-OFF        |
| Light source                | LED           |
| Type of LED                 | COB           |
| Colour temperature (K)      | 3000          |
| Colour consistency (SDCM)   | SDCM<3        |
| CRI                         | 80            |
| IK                          | IK05          |

Dimensions

Product dimensions (mm)  $\varnothing 75 \times 98 \times 240 \text{ mm}$

Scheme



Photometry

