



UP&DOWNT

UP&DOWNT is a wall light with round design emitting light up and down. With a size of Ø100mmx280mm has a power of 2x12W and two reflectors up&down of 22 degrees beam angle. With a real lumen output of 2158lm, and an efficiency of 89.92lm/W. Is made in Die Cast Aluminium Body, Tempered Glass Cover and has an IP65 and an IK10 degree of protection. DALI driver. Finished in White color.

| | |
|------------------|------------------------|
| Item code | 86.OW09.3323.01 |
|------------------|------------------------|

| | |
|---------------------|----------------|
| Product type | Outdoor |
|---------------------|----------------|

| | |
|-----------------|-------------------|
| Category | Wall Light |
|-----------------|-------------------|

| | |
|---------------|---------------------|
| Family | UP&DOWNT |
|---------------|---------------------|

Pictograms



| | |
|----------------|--|
| Product | |
|----------------|--|

| | |
|-----------------------|-----------|
| Real power (W) | 12 |
|-----------------------|-----------|

| | |
|--------------------------------|-------------|
| Real luminous flux (Lm) | 2158 |
|--------------------------------|-------------|

| | |
|-----------------------------------|--------------|
| Luminous efficiency (Lm/W) | 89.92 |
|-----------------------------------|--------------|

| | |
|-----------------------|-----------|
| Beam angle (°) | 22 |
|-----------------------|-----------|

| | |
|----------------------|----------------------|
| Life time (h) | 50000h L70B10 |
|----------------------|----------------------|

| | |
|-----------|-----------|
| IP | 65 |
|-----------|-----------|

| | |
|------------------------------------|----------------|
| Electrical class insulation | Class I |
|------------------------------------|----------------|

| | |
|---------------|--------------|
| Colour | White |
|---------------|--------------|

| | |
|------------------------------|------------|
| Control gear included | Yes |
|------------------------------|------------|

| | |
|---------------------|-------------|
| Control gear | DALI |
|---------------------|-------------|

| | |
|-------------------------------|-------------|
| Colour temperature (K) | 3000 |
|-------------------------------|-------------|

| | |
|----------------------------------|------------------|
| Colour consistency (SDCM) | SDCM<3 |
|----------------------------------|------------------|

| | |
|------------|-----------|
| CRI | 80 |
|------------|-----------|

| | |
|-----------|-----------|
| IK | 10 |
|-----------|-----------|

Scheme

