



### Dimensions

**Product dimensions (mm)** 32x83x1000mm

### Scheme



### Snake 3DMX

Lavov outdoor spot light from the family Snake 3DMX with a power of 54W and a 10 degrees beam angle. Surface mounted installation With a total lumen output of 4050lm and a luminous efficiency of 75lm/W. Driver DMX512/24pixel not included .Made in Die cast aluminum body + PC transparent cover. Powder coated,. Class III isolation. IP65 and IK08 . Mains voltage DC 24V. Finished in grey colour. CCT 2700K.CRI80

|                     |                                                                                                                                                                                        |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Item code</b>    | <b>86.OW09.4210.03</b>                                                                                                                                                                 |
| <b>Product type</b> | <b>Outdoor</b>                                                                                                                                                                         |
| <b>Category</b>     | <b>Wall Washer</b>                                                                                                                                                                     |
| <b>Family</b>       | <b>Snake 3</b>                                                                                                                                                                         |
| <b>Subfamily</b>    | <b>Snake 3DMX</b>                                                                                                                                                                      |
| <b>Pictograms</b>   | <div>50 Hz</div> <div>60 Hz</div> <div>850°</div> <div>CRI 80</div> <div>SDCM 3</div> <div>CE</div> <div>Driver EXCL.</div> <div>50000h L70B10</div> <div>IP 65</div> <div>IK 08</div> |

|                                    |                       |
|------------------------------------|-----------------------|
| <b>Product</b>                     |                       |
| <b>Real power (W)</b>              | <b>54</b>             |
| <b>Real luminous flux (Lm)</b>     | <b>#VALUE!</b>        |
| <b>Luminous efficiency (Lm/W)</b>  | <b>75</b>             |
| <b>Beam angle (°)</b>              | <b>10</b>             |
| <b>Life time (h)</b>               | <b>50000h L70B10</b>  |
| <b>IP</b>                          | <b>65</b>             |
| <b>Electrical class insulation</b> | <b>Class III</b>      |
| <b>Electrical feeding</b>          | <b>DC 24V</b>         |
| <b>Colour</b>                      | <b>grey</b>           |
| <b>Control gear included</b>       | <b>not included</b>   |
| <b>Control gear</b>                | <b>DMX512/24pixel</b> |
| <b>Power Factor</b>                | <b>DMX512/24pixel</b> |
| <b>Flicker Free</b>                | <b>DMX512/24pixel</b> |
| <b>Light source</b>                | <b>LED</b>            |
| <b>Type of LED</b>                 | <b>Osram 3030</b>     |
| <b>Average life time (h)</b>       | <b>50000h L70B10</b>  |
| <b>Colour temperature (K)</b>      | <b>2700</b>           |
| <b>Colour consistency (SDCM)</b>   | <b>SDCM3</b>          |
| <b>CRI</b>                         | <b>80</b>             |
| <b>IK</b>                          | <b>8</b>              |