



### WDOWN

Lavov outdoor wall light from the family WDOWN with a power of 40W and a optic distribution 15°/40°. With a total lumen output of 3250lm and an efficiency of 81,25lm/W. Manufactured in Die Cast Aluminium Body, Tempered Glass Cover and finished in Grey colour.

|                  |                        |
|------------------|------------------------|
| <b>Item code</b> | <b>86.OW20.2331.03</b> |
|------------------|------------------------|

|                     |                |
|---------------------|----------------|
| <b>Product type</b> | <b>Outdoor</b> |
|---------------------|----------------|

|                 |                   |
|-----------------|-------------------|
| <b>Category</b> | <b>Wall Light</b> |
|-----------------|-------------------|

|               |              |
|---------------|--------------|
| <b>Family</b> | <b>WDOWN</b> |
|---------------|--------------|


**Pictograms**



### Dimensions

**Product dimensions (mm)**    **Ø160mmx183mm**

### Scheme



### Product

|                       |           |
|-----------------------|-----------|
| <b>Real power (W)</b> | <b>40</b> |
|-----------------------|-----------|

|                                |             |
|--------------------------------|-------------|
| <b>Real luminous flux (Lm)</b> | <b>3250</b> |
|--------------------------------|-------------|

|                                   |              |
|-----------------------------------|--------------|
| <b>Luminous efficiency (Lm/W)</b> | <b>81.25</b> |
|-----------------------------------|--------------|

|                       |                |
|-----------------------|----------------|
| <b>Beam angle (°)</b> | <b>15°/40°</b> |
|-----------------------|----------------|

|                      |                      |
|----------------------|----------------------|
| <b>Life time (h)</b> | <b>50000h L70B10</b> |
|----------------------|----------------------|

|           |           |
|-----------|-----------|
| <b>IP</b> | <b>65</b> |
|-----------|-----------|

|                                    |                |
|------------------------------------|----------------|
| <b>Electrical class insulation</b> | <b>Class I</b> |
|------------------------------------|----------------|

|               |             |
|---------------|-------------|
| <b>Colour</b> | <b>Grey</b> |
|---------------|-------------|

|                   |              |
|-------------------|--------------|
| <b>Chip Brand</b> | <b>OSRAM</b> |
|-------------------|--------------|

|                              |            |
|------------------------------|------------|
| <b>Control gear included</b> | <b>Yes</b> |
|------------------------------|------------|

|                     |               |
|---------------------|---------------|
| <b>Control gear</b> | <b>ON-OFF</b> |
|---------------------|---------------|

|                               |             |
|-------------------------------|-------------|
| <b>Colour temperature (K)</b> | <b>3000</b> |
|-------------------------------|-------------|

|                                  |                  |
|----------------------------------|------------------|
| <b>Colour consistency (SDCM)</b> | <b>SDCM&lt;3</b> |
|----------------------------------|------------------|

|            |           |
|------------|-----------|
| <b>CRI</b> | <b>80</b> |
|------------|-----------|

|           |             |
|-----------|-------------|
| <b>IK</b> | <b>IK10</b> |
|-----------|-------------|