



## E-PANEL

Lavov recessed fixture from the family E-PANEL with a power of 35W and a beam angle of120 degreeswith a real lumen output of 4200 lm and an efficiency of 120lm/W. Driver DALI and CCT 3000K.


| ltem code    | 86.R001.1303.01<br>Indoor<br>Recessed Fixtures |  |  |
|--------------|--|--|--|
| Product type |  |  |  |
| Category     |  |  |  |
| Family       | E-PANEL  |  |  |
| Pictograms   | □ 220 v >  CRI<br>240 v 850° CRI C€            |  |  |
|              | Driver On Emerg. IP<br>INCL. Off Ih 20         |  |  |
|              | 50000h<br>L80 <b>B</b> 10                      |  |  |

## Dimensions

**Product dimensions (mm)** 

596x596x11

## Scheme



| Product                    |               |
|----------------------------|---------------|
| Real power (W)             | 35            |
| Real luminous flux (Lm)    | 4200          |
| Luminous efficiency (Lm/W) | 120           |
| Beam angle (º)             | 120           |
| Life time (h)              | 50000h L80B10 |
| IP                         | 20 / 40       |
| Colour                     | White         |
| Chip Brand                 | Seoul         |
| Control gear included      | Yes           |
| Control gear               | DALI          |
| Colour temperature (K)     | 3000          |
| Colour consistency (SDCM)  | SDCM<3        |
| CRI                        | 80            |

