



E-PANEL

Lavov recessed fixture from the family E-PANEL with a power of 55W and an optics with UGR19with a real lumen output of 6160 lm and an efficiency of 112lm/W. Driver On-Off and CCT 4000K.

| Item code | 86.R001.3491.01 | | | | |
|--------------|----------------------------|--|--|--|--|
| Product type | Indoor Recessed Fixtures | | | | |
| Category | | | | | |
| Family | E-PANEL | | | | |
| Subfamily | E-PANEL | | | | |
| Pictograms | 220 V | | | | |
| | oriver INCL. Off Emerg. IP | | | | |
| | 50000h L80 B 10 | | | | |

| Product | | |
|----------------------------|---------------|--|
| Real power (W) | 55 | |
| Real luminous flux (Lm) | 6160 | |
| Luminous efficiency (Lm/W) | 112 | |
| Beam angle (º) | 86.1 | |
| Life time (h) | 50000h L80B10 | |
| IP | 20 / 40 | |
| Colour | White | |
| U. G. R | <19 | |
| Chip Brand | Seoul | |
| Control gear included | Yes | |
| Control gear | On-Off | |
| Colour temperature (K) | 4000 | |
| Colour consistency (SDCM) | SDCM<3 | |
| CRI | 80 | |

| Dimensions | |
|-------------------------|-------------|
| Product dimensions (mm) | 1196x296x11 |

| C - l | | |
|--------|--|--|
| Scheme | | |

