




### TUBULAR-S


Lavov surface mounted downlight from the family TUBULAR-S with a power of 25W and an optics 50 degrees beam angle. CCT 4000K. With a total lumen output of 2050lm and an efficacy of 82lm/W . Made in Die Cast Aluminum and finished in White color. ON-OFF driver.

|                     |   |
|---------------------|---|
| <b>Item code</b>    | <b>86.SD01.2431.01</b>  |
| <b>Product type</b> | <b>Indoor</b>   |
| <b>Category</b>     | <b>Surface Downlights</b>   |
| <b>Family</b>       | <b>TUBULAR-S</b>  |
| <b>Pictograms</b>   |  |

### Dimensions

**Product dimensions (mm)**    **Ø169X139 mm**

### Scheme



### Product

|                                   |                      |
|-----------------------------------|----------------------|
| <b>Real power (W)</b>             | <b>25</b>            |
| <b>Real luminous flux (Lm)</b>    | <b>2050</b>          |
| <b>Luminous efficiency (Lm/W)</b> | <b>82</b>            |
| <b>Beam angle (°)</b>             | <b>50</b>            |
| <b>Life time (h)</b>              | <b>50000h L80B10</b> |
| <b>IP</b>                         | <b>IP20</b>          |
| <b>Colour</b>                     | <b>White</b>         |
| <b>Chip Brand</b>                 | <b>Philip</b>        |
| <b>Control gear included</b>      | <b>Yes</b>           |
| <b>Control gear</b>               | <b>ON-OFF</b>        |
| <b>Average life time (h)</b>      | <b>40</b>            |
| <b>Colour temperature (K)</b>     | <b>4000</b>          |
| <b>Colour consistency (SDCM)</b>  | <b>SDCM&lt;3</b>     |
| <b>CRI</b>                        | <b>80</b>            |

### Photometry

