



TUBULAR-S

Lavov surface mounted downlight from the family TUBULAR-S with a power of 30W and an optics 50 degrees beam angle. CCT 3000K. With a total lumen output of 2500lm and an efficacy of 83,33lm/W . Made in Die Cast Aluminum and finished in Black color. ON-OFF driver.

Item code	86.SD01.3331.02
------------------	------------------------

Product type	Indoor
---------------------	---------------

Category	Surface Downlights
-----------------	---------------------------

Family	TUBULAR-S
---------------	------------------

Pictograms	
-------------------	---

Product

Real power (W)	30
-----------------------	-----------

Real luminous flux (Lm)	2500
--------------------------------	-------------

Luminous efficiency (Lm/W)	83.33
-----------------------------------	--------------

Beam angle (°)	50
-----------------------	-----------

Life time (h)	50000h L80B10
----------------------	----------------------

IP	IP20
-----------	-------------

Colour	Black
---------------	--------------

Chip Brand	Philip
-------------------	---------------

Control gear included	Yes
------------------------------	------------

Control gear	ON-OFF
---------------------	---------------

Average life time (h)	30
------------------------------	-----------

Colour temperature (K)	3000
-------------------------------	-------------


Colour consistency (SDCM)	SDCM<3
----------------------------------	------------------

CRI	80
------------	-----------

Dimensions

Product dimensions (mm)	Ø200X139 mm
--------------------------------	--------------------

Scheme



Photometry

