


## SQUARE-S

Lavov surface downlight from the family SQUARE-S B with a power of 25W and a beam angle of 60º. Finished in White colour. Dimensions 92x92x100mm.With a total lumen output of 2000lm and a luminous efficacy of 80lm/W. Made in Die cast aluminium. Driver DALI. CCT 4000K. IP65.

| | |
|---|---|
| **Item code** | **86.SD03.2433.01** |
| **Product type** | **Indoor** |
| **Category** | **Surface Downlights** |
| **Family** | **SQUARE-S** |
| **Pictograms** |  |

| **Dimensions** | |
|---|---|
| **Product dimensions (mm)** | **92x92x100mm** |

**Scheme**




| **Product** | |
|---|---|
| **Real power (W)** | **25** |
| **Real luminous flux (Lm)** | **2000** |
| **Luminous efficiency (Lm/W)** | **80** |
| **Beam angle (º)** | **60** |
| **Life time (h)** | **50000h L80B10** |
| **IP** | **IP65** |
| **Colour** | **White** |
| **Control gear included** | **Yes** |
| **Control gear** | **DALI** |
| **Light source** | **LED** |
| **Type of LED** | **COB** |
| **Colour temperature (K)** | **4000** |
| **Colour consistency (SDCM)** | **SDCM3** |
| **CRI** | **80** |